II.   CLAIM AMENDMENTS

1. (Currently Amended) A method for presenting information contained in user messages in a user interface of a multimedia terminal, in which method the user message comprises at least one component, and which user message is transmitted to the multimedia terminal in a multimedia message transmission system, wherein in the method, a presentation model is formed to contain information related to at least one component connected with the user message, said presentation model is supplemented with a reference to the location of data related to presenting at least one component in said user message, and said presentation model is added to said user message.

2. (Previously Presented) The method according to claim 1, wherein said presentation model is set up in the terminal which transmits the message.

3. (Previously Presented) The method according to claim 1, wherein said multimedia message transmission system comprises a multimedia message service center, in which messages addressed to the multimedia terminal are received to be transmitted further to the multimedia terminal, and the presentation model is set up in the multimedia message service center.

4. (Previously Presented) The method according to claim 1, wherein said presentation model is formed by using the SMIL format.

5. (Previously Presented) The method according to claim 1,

2

wherein said data related to presenting the component comprises said component.

6. (Previously Presented) The method according to claim 1, wherein said data related to presenting the component comprises the search address of said component.

7. (Previously Presented) The method according to claim 1, wherein the user interface of the terminal for presenting the message comprises at least a display, at least one component comprises visual information, and said presentation model is also supplemented with information about placing the component on said display.

8. (Previously Presented) The method according to claim 1, wherein the user interface of the terminal for presenting the message comprises at least audio means, at least one component comprises audio information, and said presentation model is also supplemented with data about converting the component into audio information in the audio means.

9. (Previously Presented) The method according to claim 1, wherein said presentation model is also supplemented with information about the time of effect of the component, such as a display time of an image or a text, or a time of repeating a sound.

10. (Previously Presented) The method according to claim 9, wherein the message comprises at least two components, and said presentation model is also supplemented with information about the mutual synchronization of the components.

3

11. (Previously Presented) The method according to 1, wherein the message comprises at least two pages, and said presentation model is supplemented with data about the order of presenting the pages.

12. (Currently Amended) A system for transmitting multimedia user messages, comprising means for transmitting a user message to a multimedia terminal which comprises a user interface for presenting information contained in the user messages, and each user message contains at least one component, wherein the system comprises means for forming a presentation model in the user message, the presentation model comprising information related to presenting at least one component in said user message, said presentation model is supplemented with a reference to the location of data related to presenting at least one component in said user message, and the system comprises means for attaching said presentation model in said user message.

13. (Previously Presented) The system for transmitting multimedia messages according to claim 12, wherein the terminal which transmits the message comprises means to set up the presentation model.

14. (Previously Presented) The system for transmitting multimedia messages according to claim 12, further comprising a multimedia message service center which comprises means for receiving messages addressed to the multimedia terminal, means for transmitting the messages further to the multimedia terminal, and means for setting up a presentation model.

15. (Previously Presented) The system for transmitting multimedia messages according to claim 12, wherein said presentation model

4

is formed by using the SMIL format.

16. (Previously Presented) The system for transmitting multimedia messages according to claim 12, in which the user interface of the terminal presenting the message comprises at least a display, wherein at least one component comprises visual information, and said presentation model is also supplemented with data about placing the component on said display.

17. (Previously Presented) The system for transmitting multimedia messages according to claim 12, in which the user interface of the terminal presenting the message comprises at least audio means, wherein at least one component comprises audio information, and said presentation model is also supplemented with data about converting the component into audio information in audio means.

18. (Previously Presented) The system for transmitting multimedia messages according to claim 12, wherein said presentation model is also supplemented with information about the time of effect of the component, such as the time of displaying an image or a text, or the time of repeating a sound.

19. (Previously Presented) The system for transmitting multimedia messages according to claim 12, wherein the message comprises at least two multimedia pages, and said presentation model is supplemented with information about the order of presenting the multimedia pages.

20. (Previously Presented) The system for transmitting multimedia messages according to claim 12, wherein the message comprises at least two multimedia pages, and said presentation model is sup-

5

plemented with information about the order of presenting the multimedia pages.

21. (Currently Amended) A transmitting multimedia terminal which comprises means for forming <u>user</u> messages of at least one component, and means for transmitting the <u>user</u> messages, wherein the multimedia terminal also comprises means for forming a presentation model in the <u>user</u> message, which presentation model comprises information related to presenting at least one component added in the <u>user</u> message, and which presentation model is supplemented with a reference to the location of information related to presenting at least one component in said <u>user</u> message.

22. (Currently Amended) A receiving multimedia terminal which comprises means for receiving <u>user</u> messages, and a user interface for presenting information contained in the <u>user</u> messages, and each <u>user</u> message contains at least one component, wherein the multimedia terminal also comprises means for interpreting a presentation model formed in a <u>user</u> message, which presentation model comprises information related to presenting at least one component, which presentation model is supplemented with a reference to the location of information related to presenting at least one component in said <u>user</u> message, and the multimedia terminal comprises means for finding out said presentation model from said <u>user</u> message.

23. (Previously Presented) The multimedia terminal according to claim 21, wherein it is a mobile terminal .

6